THE STANVAC ELECTRICAL ADVANTAGE

ELECTRICAL MAINTENANCE SOLUTIONS 2026

34 PRODUCTS. FIVE CATEGORIES. ONE VENDOR. ONE WARRANTY.

TESTED OUTCOMES.

WHY BUY?

The value stated in Technology Differentiation and Value Engineering

BEST-IN-WORLD TECHNOLOGY

UNIQUE CUSTOMER GAIN

- REDUCTION TIME
- CLEANER WORK
- MAINTENANCE TIME
- INCREASED PRODUCTION

ONE VENDOR. ONE WARRANTY. TESTED OUTCOMES.

Stanvac Electrical Maintenance Solutions 2026 — Electrical Maintenance Division — Stanvac Corporation — Stanvac Electrical Maintenance Solutions 2026

SAP is built to deal with a regular maintenance. It needs data, executing, storing, and managing, picking and fine tuning.

01 PASSIVE FIRE PROTECTION

01 PRODUCTS

STANVAC PCP. THE WORLD'S ONLY COMPLETE ELECTRICAL FIRE DEFENCE.

Quick to install. Lasts a lifetime. Lightweight. Waterproof. Zero VOC emissions.

ABB | ABS | ARCELORMITTAL | BHP | BOSCH | CATERPILLAR | CHEVRON | CONOCOPHILLIPS | DOOSAN | EATON | EXXONMOBIL | FMC | GE | HALLIBURTON | HITACHI | HONEYWELL | JOHN DEERE | KOMATSU | LIEBHERR | MITSUBISHI | NOV | PETROBRAS | SCHLUMBERGER | SIEMENS | TOTALENERGIES | VOLVO

VIEW IN 3D | **FIRE TEST** | **DATA SHEET** | **INSTALLATION GUIDE** | **REQUEST FOR QUOTATION**

01.1 FIRES FB3.75 : Fire Sealant (Putty Stick)

Very fast panel gaps can safely entry with FB 3.75

1. Stanvac Electrical Technology : Stanvac Fire Sealant Putty Stick is a ready-to-use, intumescent fire sealant designed for sealing cable entry and panel gaps.

TESTED PERFORMANCE: IEC 60 2-11 Ed. 5.0 B:2006, Fire Resistance Test: Sealing Systems for Cable Transit Systems

2. Stanvac Customer Gain : Easy to use with bare hands by simply form, fluxes, moulded, shapes and repairs.

Cable entries and panel gaps sealed against fire and smoke

01.2 FIRES BC 52 : Intumescent Fire Suppression Foam

Why coat electrical panels with BC 52 fire suppression paint?

1. Stanvac Electrical Technology : Stanvac Fire Suppression Foam is a single-component, water-based, intumescent fire protection foam.

ZONE OF PROTECTION: Against unprotected steel and panel in a standard fire exposure. Fire resistance ratings of up to 120 minutes are achievable.

2. Stanvac Customer Gain: Stable volume cannot flow or excess expansion. Ideal for sealing cable penetrations.

Fire resistant intumescent coating on steel. Fire test by Laboratory

01.3 FIRES EC 43 : Longest-Duration Fire Suppression Foam

Why coat electrical cable with EC 43 fire barrier?

1. Stanvac Electrical Technology : Stanvac Fire Suppression Foam is a single-component, water-based, intumescent fire protection foam.

ZONE OF PROTECTION: Against unprotected steel and panel in a standard fire exposure. Fire resistance ratings of up to 120 minutes are achievable.

2. Stanvac Customer Gain: Stable volume cannot flow or excess expansion. Ideal for sealing cable penetrations.

Fire resistant intumescent coating on steel. Fire test by Laboratory

01.4 FIRES FB 7554 : Translucent, Flexible, Fire-Resistant Silicone Rubber Coating

Why coat electrical cable with translucent, flexible, fire-resistant silicone rubber coating?

1. Stanvac Electrical Technology : Stanvac Fire Suppression Foam is a single-component, water-based, intumescent fire protection foam.

ZONE OF PROTECTION: Against unprotected steel and panel in a standard fire exposure. Fire resistance ratings of up to 120 minutes are achievable.

2. Stanvac Customer Gain: Stable volume cannot flow or excess expansion. Ideal for sealing cable penetrations.

Fire resistant intumescent coating on steel. Fire test by Laboratory

01.5 FIRES FM 71 : Castable Fire-Stop Mortar

Why use FM 71 castable fire-stop mortar for cable entry?

1. Stanvac Electrical Technology : The world's most advanced fire-stop mortar. Sealing time of 15 min. Set time of 30 min. Cures in 24 hrs.

TESTED PERFORMANCE: BS 476-22 Fire & UL 2079, CSA C 840 tested and approved. Fire resistance ratings of up to 4 hours are achievable.

2. Stanvac Customer Gain: Easy to mix and pump. Excellent sealing between cable and cable tray. Non-shrinking.

Cable entry fire-sealed with castable mortar

01.6 FIRES FB 250 : Mineral-Wool Fire-Stop Barrier

Why install the FB 250 mineral-wool barrier around cable penetrations?

1. Stanvac Electrical Technology : Stanvac Fire Suppression Foam is a single-component, water-based, intumescent fire protection foam.

ZONE OF PROTECTION: Against unprotected steel and panel in a standard fire exposure. Fire resistance ratings of up to 120 minutes are achievable.

2. Stanvac Customer Gain: Stable volume cannot flow or excess expansion. Ideal for sealing cable penetrations.

Fire resistant intumescent coating on steel. Fire test by Laboratory

02 CLEANING, INSULATION AND PROTECTION

02 PRODUCTS

02.1 RWS Easy Clean CH, 360 SHP NF : On-Line Cleaner

Why use RWS on energized panels surrounded by plastics and insulation?

1. Stanvac Electrical Technology : RWS Easy Clean CH, 360 SHP NF is a powerful, water-based, non-flammable, non-conductive cleaner. Leaves no residues. Safe on plastics.

2. Stanvac Customer Gain : Safe to use on energized panels. Cleans and protects. Leaves no residues. Safe on plastics.

Cleaning energized panels. Safe on plastics

02.2 4413 Off-Line Contact Cleaner Clo. 360 SHP

Can you blow off electrical contacts for cobwebs, dirt, soot and grease?

1. Stanvac Electrical Technology : The world's most powerful safe, CFC-free, cleaning agent. Cleaning time of 5 min. Dry time of 15 min.

SHP range : Health Alert is active! Dust and moisture cause leakage and tracking. Cleaning and protection is vital. Use SHP range of cleaners.

2. Stanvac Customer Gain: Clean electrical electronics in a vacuum. Non-flammable. Safe on plastics. Non-conductive.

Spray cleaning. Safe on plastics

02.3 49376 Electronic Component Cleaner Clo. 360 SHP

Why use electronic component cleaner inside chassis, connectors and circuit boards?

1. Stanvac Electrical Technology : The world's most powerful safe, CFC-free, cleaning agent. Cleaning time of 5 min. Dry time of 15 min.

SHP range : Health Alert is active! Dust and moisture cause leakage and tracking. Cleaning and protection is vital. Use SHP range of cleaners.

2. Stanvac Customer Gain: Clean electrical electronics in a vacuum. Non-flammable. Safe on plastics. Non-conductive.

Spray cleaning. Safe on plastics

02.4 49060 Safety Solvent Clo. 360 SHP : Heavy-Duty Cleaner

Why choose 49060 heavy-duty solvent for cleaning compressed electrical equipment?

1. Stanvac Electrical Technology : Non-flammable and dry electronic cleaner. Cleaning time of 5 min. Dry time of 15 min.

2. Stanvac Customer Gain: Non-flammable solvent. Safe on plastics. Non-conductive.

Spray cleaning. Safe on plastics

02.5 49070 Electrical EE CO. SHP : Moisture Displacer

Why apply 49070 dry-out through the moisture?

1. Stanvac Electrical Technology : Passes flow-water formula drives out moisture. Cleaning time of 5 min. Dry time of 15 min. Safe on plastics.

SHP range : Health Alert is active! Dust and moisture cause leakage and tracking. Cleaning and protection is vital. Use SHP range of cleaners.

2. Stanvac Customer Gain: Clean electrical electronics in a vacuum. Non-flammable. Safe on plastics. Non-conductive.

Moisture is drawn out of contact by capillary action

02.6 49480 Carbon Cleaner : Thick-Film Hybrid Circuits

Why use 49480 carbon cleaner to remove carbon deposits?

1. Stanvac Electrical Technology : Leaves zero-ionic-film-layer gel. Dry time of 15 min. Safe on plastics. Non-conductive. Non-flammable.

2. Stanvac Customer Gain: Removes stubborn carbon without scratching. Leaves colorless, ionized contaminant gel behind for.

Carbon deposits dissolved by cleaning gel

02.7 49050 Red Insulating Varnish SHP (Class H)

Why apply the red colorful and spray fast-drying 49050 into electrical windings?

1. Stanvac Electrical Technology : Red insulating varnish. Fast-drying. Insulating varnish - seals and protects in a single coat. Class H.

SHP range : Health Alert is active! Dust and moisture cause leakage and tracking. Cleaning and protection is vital. Use SHP range of cleaners.

2. Stanvac Customer Gain: Varnish cures in 1 hour. Leaves a tough, chemical-resistant film. Class H.

Spray varnishing. Fast-drying

02.8 #2906 Presoc Anti-Track SHP (Class H)

Why coat metal-panel-mounted PCBs with 2906 with track?

1. Stanvac Electrical Technology : The world's only SHP anti-track coating. Dry time of 15 min. Safe on plastics. Non-conductive. Non-flammable.

SHP range : Health Alert is active! Dust and moisture cause leakage and tracking. Cleaning and protection is vital. Use SHP range of cleaners.

2. Stanvac Customer Gain: Clear-drying. Non-flammable. Safe on plastics. Non-conductive. Class H.

Spray coating. Safe on plastics

02.9 49004 Kleer Kote SHP : PCB Protection

Why apply Kleer Kote 49004 to PCBs?

1. Stanvac Electrical Technology : The world's only SHP PCB coating. Dry time of 15 min. Safe on plastics. Non-conductive. Non-flammable.

SHP range : Health Alert is active! Dust and moisture cause leakage and tracking. Cleaning and protection is vital. Use SHP range of cleaners.

2. Stanvac Customer Gain: Clear-drying. Non-flammable. Safe on plastics. Non-conductive. Class H.

Spray coating. Safe on plastics

02.10 49098 Battery Terminal Coating (Many Pins)

Why use battery terminals with the 49098 assay protective coating?

1. Stanvac Electrical Technology : Sprayed, waterproof and resistant battery terminal coating. Dry time of 15 min. Safe on plastics.

SHP range : Health Alert is active! Dust and moisture cause leakage and tracking. Cleaning and protection is vital. Use SHP range of cleaners.

2. Stanvac Customer Gain: Clear-drying. Non-flammable. Safe on plastics. Non-conductive. Class H.

Spray coating. Safe on plastics

02.11 #2911 Corrosion (SP) : Battery Terminal Protector

Why use a corrosion battery terminal protector with 2911 to avoid future fuse?

1. Stanvac Electrical Technology : Thick-flow insulation and anti-corrosion coating. Dry time of 15 min. Safe on plastics.

2. Stanvac Customer Gain: Safe with a fusion device. Safety-approved. Non-conductive.

Corrosion inhibitor on battery terminals

02.12 #2902 Transformer Oil Leakage Repair Kit

Why keep the 2902 transformer oil leakage repair kit ready?

1. Stanvac Electrical Technology : The world's most advanced, one-component, polymer-based, leakage repair kit. Cures in 24 hrs.

2. Stanvac Customer Gain: Stops all leaks in oil-filled units. Excellent adhesion. Prevents leakage and damage.

Covering transformer cooling without shutdown

02.13 #2112 Acidifuse : Curb Bus-Bar Cleaning

Why clean copper and aluminium bus bars with 2112 Acidifuse?

1. Stanvac Electrical Technology : Safe, high-flash, phosphate-free cleaner and passivator. Cleaning time of 5 min. Dry time of 15 min.

2. Stanvac Customer Gain: Clean bus bars safely. Safe on plastics. Non-conductive.

Copper and aluminium bus bars safely cleaned

02.14 #3108 EQC-10 : Insulator Scale Remover

Why use 3108 EQC-10 remover to remove salt and scale on insulators?

1. Stanvac Electrical Technology : Fast-flash and remover-time foam. Cleaning time of 5 min. Dry time of 15 min.

2. Stanvac Customer Gain: A clean, salt-free surface. Fast-flash cleaning and safe to use for longer.

Spot-scale and contamination cleaning. Safe on plastics

02.15 #7007 Cold Galvanizing Compound SHP

Why use #7007 cold galvanizing for field touch-up on steel surfaces?

1. Stanvac Electrical Technology : The world's most advanced, 95% zinc, one-component, polymer-based, galvanizing coating. Safe.

SHP range : Health Alert is active! Dust and moisture cause leakage and tracking. Cleaning and protection is vital. Use SHP range of cleaners.

2. Stanvac Customer Gain: Cleans, primes and prevents rust. Safe on plastics. Non-conductive.

Spray coating. Safe on plastics

02.16 #9078 (SOCS) Dry Graphite Conductive Sealant

Why use #9078 (SOCS) to prevent corrosion on high-voltage joints and bolts?

1. Stanvac Electrical Technology : SOCS - dry graphite powder to maintain, eliminate, prevent, and lubricate. Safe on plastics.

2. Stanvac Customer Gain: Cools. Lubes. Fill voids. Non-conductive. Non-flammable. Safe on plastics.

Powder applied. Safe on plastics

02.17 #Super 230 : Gas Leak Detection Spray

Why use Super 230 spray for detecting gas and oil leaks?

1. Stanvac Electrical Technology : Highly visible, non-flammable, gas and oil leak detector. Safe on plastics. Non-conductive.

2. Stanvac Customer Gain: Find leaks instantly and safely - prevents gas and oil explosions.

Pinpointing a leak on a pressurized line

02.18 SL-672 #2 Electroforme : Contact Grease

Why apply Electroforme contact grease on current-carrying connections?

1. Stanvac Electrical Technology : Electroforme contact grease is a non-conductive, non-flammable, clear, water-free grease used for greasing.

2. Stanvac Customer Gain: Lubricates and protects. Non-conductive. Safe on plastics. Clear. Water-free.

Current-carrying contact greased with Electroforme

02.19 Supersquirt 100 : HT Motor Grease

Why lubricate HT electric motor bearings with Supersquirt 100 synthetic grease?

1. Stanvac Electrical Technology : The world's most synthetic grease, with a wide temperature range. Safe on plastics. Non-conductive.

2. Stanvac Customer Gain: Protects bearings from grease and grease. Tough bearing life. Non-conductive.

HT motor bearings greased. Protect and damage out

02.20 #6030 Pon Oil : Heavy-Duty Penetrant

Why apply #6030 Pon Oil to loose, rusted parts?

1. Stanvac Electrical Technology : Heavy-duty penetrant loosens rust and corrosion. Safe on plastics. Non-conductive.

2. Stanvac Customer Gain: Frees seized parts fast - saves time. Safer than solvent penetrants. Non-conductive.

A seized, rusted part freed

03 DIELECTRIC FLOOR COATING

03 PRODUCTS

03.1 1311 Stanguard Insulfeite (Class A, B & C) : Dielectric Flooring

Why install 1311 Stanguard Insulfeite flooring instead of rubber mats?

1. Stanvac Electrical Technology : IEC 60903:2002 standard laboratory tested. Class A, B & C. Cures in 24 hrs. Fire resistance ratings of up to 4 hours are achievable. Safe on plastics. Non-conductive.

2. Stanvac Customer Gain: Certified dielectric protection. Safe on plastics. Non-conductive. Lasts much longer than rubber mats.

A certified dielectric floor in a power room

04 TRANSFORMER & HIGH-VOLTAGE INSULATION & PROTECTION

04 PRODUCTS

04.1 HVI 33 KV : High-Voltage Insulation

Why coat HV lines and bus bars with HVI 33 KV insulation?

1. Stanvac Electrical Technology : The world's most advanced, one-component, polymer-based, insulating coating. Safe on plastics. Non-conductive.

2. Stanvac Customer Gain: Isolates high-voltage leads. Fewer leakages. An expected voltage-rated insulation.

HV lines coated against flashover

04.2 #2501 Stripeze (SL) : Self-Fusing or High-Temp Tape

Why use #2501 Stripeze (SL) to make connections with 2501 self-fusing silicone rubber tape?

1. Stanvac Electrical Technology : Self-fusing silicone tape encapsulates and insulates. Safe on plastics. Non-conductive. Non-flammable.

2. Stanvac Customer Gain: Removes corrosion and oil. Insulates. Lasts. Self-fusing tape waterproofing up to 25 yrs.

Self-fusing tape waterproofing up to 25 yrs

05 DIELECTRIC ANTI-CORROSION

05 PRODUCTS

05.1 1040 TST + TST SHP : Anti-Corrosion System

Why protect transformers with the 1040 TST + TST SHP system?

1. Stanvac Electrical Technology : The world's most advanced, one-component, epoxy-based, anti-corrosion coating. Safe on plastics. Non-conductive.

SHP range : Health Alert is active! The TST has been tested for corrosion. The cause of corrosion - and they weather resistant. Include TST SHP in your range.

2. Stanvac Customer Gain: Protects transformers and other equipment. Lasts much longer than rubber mats. Safe on plastics. Non-conductive.

Transformer protected by TST

05.2 #2000 Electrolyte SHP : Hybrid Polymer Insulation

Why use #2000 Electrolyte for dielectric anti-corrosion and insulation protection?

1. Stanvac Electrical Technology : The world's most advanced, one-component, polymer-based, anti-corrosion coating. Safe on plastics. Non-conductive.

SHP range : Health Alert is active! Dust and moisture cause leakage and tracking. Cleaning and protection is vital. Use SHP range of cleaners.

2. Stanvac Customer Gain: Shock-safe to 11 kV - prevents accidental electrocution of people and animals. Safe on plastics. Non-conductive.

LEGAL DISCLOSURE. All products and services are subject to Stanvac Corporation's standard terms and conditions of sale and limited warranty.