52 PRODUCTS / SEVEN CATEGORIES / ONE STANDARD

THE STANVAC MECHANICAL ADVANTAGE

MECHANICAL & CIVIL MAINTENANCE SOLUTIONS 2026

ONE VENDOR. ONE WARRANTY.
OUTCOMES GUARANTEED.

STAR TECHNOLOGY / Z704 RUSTEX-NMB

RUST CONVERTED. LIFE DOUBLED.



TriArmor conversion reaches the base of every pit.

2X GRIP / 2X SYSTEM LIFE

500+ HOURS SALT SPRAY WITH EPOXY TOPCOAT

WHY BUY?

A BEST-IN-WORLD TECHNOLOGY

B UNIQUE CUSTOMER GAIN

01 SUPERIOR ANTI-CORROSION	02 COLD REPAIRS	03 AEROSOLS	04 CONCRETE REPAIRS
05 SYNTHETIC GREASES	06 BULK CLEANERS	07 REPAIR WELDING	

Four Core Technologies

NMB Nano-Molecular Bonding — covalent bonding to parent metal; will not peel.

SHP Superhydrophobic — repels corrosion-causing dust and water.

TST True Surface Tolerance — low-surface-tension primers bond to parent steel, not surface film.

FDT Fast-Drying Technology — coat a running plant; return it to service the same day.

Z704 RUSTEX underpins every anti-corrosion system and 944 wrap. ★ **Z704 RUSTEX BASE · 2× LIFE.** Exception: **ES 70 2K**.

01 Superior Anti-Corrosion

05 PRODUCTS

75% of coating failures stem from poor surface preparation; these systems use converted, sealed steel — not rust.

1. 2050 Polyhyb SHP

ONE-COMPONENT DIRECT-TO-METAL CORROSION PREVENTION

Why coat plant steel and machinery in dusty areas with 2050 Polyhyb SHP?

A) Best-in-World Technology: The world's best one-component, fast-drying, direct-to-metal hybrid co-polymer — 2–3× the life of other 1K systems; 500+ hours salt spray.

★ Z704 RUSTEX BASE · 2× LIFE Over Z704 RUSTEX–NMB: around 2× grip, 2× life — on steel you cannot blast.

Structural steel coated direct to metal — no blasting, no shutdown.

SHP edge — repels dust & water: SHP repels dust and water — high gloss retention; FDT fast drying, ideal for dusty areas.

B) Unique Customer Gain: Long-term protection for plant steel, machinery and concrete (C1–C3) — will not crack or peel for over 2 years.

External pipe lines held gloss-white through coastal, humid service.

2. 1040 TST & NMB + 727 SHP

SURFACE-TOLERANT EPOXY-PU · WET & HEAVILY RUSTED STEEL

Why specify 1040 TST + 727 SHP where the steel is wet, oily and rusted?

A) Best-in-World Technology: The world's best true surface-tolerant "low surface tension" epoxy-PU — wet and actual rust tolerance; the primer bonds to parent metal; 2,000+ hours salt spray; 1,200+ psi adhesion on ST-2 surfaces.

★ Z704 RUSTEX BASE · 2× LIFE The Z704 RUSTEX base converts every pit — around 2× adhesion, 2× life.

SHP edge — repels dust & water: The 727 topcoat repels the dust and moisture that cause corrosion.

B) Unique Customer Gain: Cooling towers, tank exteriors, pipe lines and GI protected in wet, coastal, contaminated and oil & gas areas — 3–5 years crack-free.

Acid-plant structural steel under a glass-flake novolac armour.

3. 1040 TST & NMB + 718 EGF + 727 SHP

ACID, CHEMICAL & C5 MARINE ATTACK SYSTEM

Why build in 718 EGF glass-flake novolac for acid-attacked and marine steel?

A) Best-in-World Technology: The world's best acid-defence system — MIO + glass-flake novolac + PU; 3,000+ hours salt spray; 6 months' immersion in 98% H_2SO_4 and 33% HCl.

★ Z704 RUSTEX BASE · 2× LIFE Z704 RUSTEX neutralises the residual salt and acid — roughly double the life above it.

SHP edge — repels dust & water: The 727 topcoat stays clean and glossy in acid-fume air.

B) Unique Customer Gain: Acid-fume areas, gypsum plants, paper mills and acid bunds — will not crack, peel or rust for 3 to 5 years.

Hot manifold pipework insulated in a thin ceramic film.

4. ES 70 2K

CERAMIC THERMAL INSULATION COATING · TO 600 °C

Why insulate manifolds, furnaces, exchangers and pre-heaters with ES 70 2K?

A) Best-in-World Technology: The world's best ambient-curing ceramic insulation coating — air-filled ceramic microspheres in silicone co-polymer resin; no post-heating, no peeling off; to 600 °C; minimum 2× life.

B) Unique Customer Gain: Radiation heat loss cut, condensation prevented — energy saved; high-temperature corrosion held off manifolds, furnaces, exchangers, pre-heaters.

Anti-wear ceramic troweled onto an eroded casing — flow restored.

5. 1190 Stangard + 731 ER Xtream (Nano)

EROSION, ABRASION & CAVITATION DEFENCE · NMB

Why surface pump casings, chutes, elbows and cyclones with 1190 and 731?

A) Best-in-World Technology: 1190 — brushable ceramic nano-particle top coating, surfacing pump casings to enhance flow; 731 ER Xtream — fibre-reinforced ceramic-zirconium NMB putty for fine-particle abrasion erosion.

★ Z704 RUSTEX BASE · 2× LIFE On a Z704 RUSTEX-converted base the ceramic holds around 2× longer.

B) Unique Customer Gain: Pump housings, chutes, elbows, cyclones and material-handling and crushing equipment rebuilt and protected against erosive and pneumatic abrasive environments.

02 Cold Repairs — Metal Rebuild & Pipe Re-Strengthening

08 PRODUCTS

Permanent repairs — no hot work, no welding permit, no shutdown. Every one built on NMB.

A leaking, corroded line wrapped and re-strengthened in place.

6. #944 Synthoglass Wrap

LIVE PIPE RE-STRENGTHENING SYSTEM

Why keep 944 Synthoglass on site for cracked, leaking and corroded pipe?

A) Best-in-World Technology: The world's best pipe re-strengthening wrap — separate PU activator, no shelf-life or pot-life issue; ASME PCC-2; 45 kg pressure; applies wet.

★ Z704 RUSTEX BASE · 2× LIFE Wrapped over Z704 RUSTEX-converted steel — around 2× adhesion, 2× life.

944(A) 2″×5 ft · 944(B) 4″×15 ft · 944(C) 8″×50 ft. Also for tankage and floating roofs.

B) Unique Customer Gain: Cracked, leaking and corroded pipe re-strengthened in place — the emergency, quick-action repair.

A permanent steel repair, hand-moulded from a single stick.

7. Z801 Faststeel Epoxy Stick

EMERGENCY METAL REPAIR

Why keep Z801 Faststeel in every toolbox and maintenance van?

A) Best-in-World Technology: Fast-setting, industrial-strength NMB polymer in a hand-mixable stick — no measuring, no tools; bonds instantly with superior strength.

B) Unique Customer Gain: Steel repaired permanently on the spot, by anyone — mistake-proof.

8. Z805 Aquamend Epoxy Stick

DAMP, WET & UNDERWATER REPAIR

Why reach for Z805 Aquamend when the surface is damp or submerged?

A) Best-in-World Technology: A patented hand-mixable NMB speciality epoxy putty — applies underwater, fresh or salt water.

B) Unique Customer Gain: Repairs on damp, wet and underwater surfaces — bonds tenaciously to metal, concrete, glass, most plastics.

A wet pipe surface mended without draining the line.



Paste-grade steel putty flowing into a cracked casing.

9. Z711(P) Quicksteel Epoxy Putty NMB

OVERLAYING, LEAK SEALING & CRACK FILLING

Why choose Z711(P) for overlaying, leak sealing and crack filling?

A) Best-in-World Technology: The world's best fast-setting 1:1 steel-filled putty in a unique paste consistency for very effective overlaying — sets in 5 minutes, cures in 1 hour; 260 °C; sets up underwater.

B) Unique Customer Gain: Overlaying, leak sealing, cracks and holes — guaranteed performance; flows completely into the defect.

A corroded pipe section rebuilt and troweled smooth — no replacement.

10. 815 Stangard Steel Putty (SPL) — NMB

UNIVERSAL METAL REBUILDING

Why rebuild worn and corroded metal with 815 SPL instead of replacing?

A) Best-in-World Technology: The world's best universal repair putty — unique impact resistance, high-temperature resistance and high machinability; steel-alloy filled, rebuilds metal; repairs to 250 °C.

B) Unique Customer Gain: Corrosion damage and pitting eliminated — pipes, castings, pipe supports and pads, valves, flanges, impellers, tank pontoons and roofs rebuilt in place. Takes impact.

Companion · Z824 Glass-Fibre Tape · 50 mm × 2.5 m. Reinforcement tape for Z711(P) and 815 (SPL) where the repair must carry load.



The bond that pulled a 17-tonne tractor and trailer.

11. #Z730 Steelweld (A + B)

ULTRA-STRONG HIGH-TEMPERATURE REBUILD

Why choose Z730 Steelweld for heavy, high-stress, high-temperature rebuilds?

A) Best-in-World Technology: The world's best ultra-strong high-temperature putty — rated 250 to above 300 °C; machines by grinding, tapping, drilling.

B) Unique Customer Gain: Bearing housings, keyways, scored shafts, machine beds and hot pipelines brought back to size — withstands extreme temperature fluctuation.

Bi-metallic corrosion, structural loss, cavitation, erosion — all rebuilt.

12. 1170 Stangard Ceramic-Metal Rebuild Putty — NMB

CONDENSER, EXCHANGER & PUMP REBUILD

Why rebuild condenser tube sheets, water boxes and pump internals with 1170?

A) Best-in-World Technology: NMB bonds even on ST 2/ST 3 hand-cleaned steel; a silicon-steel alloy matrix resists cavitation, erosion and corrosion.

Overcoat with 1180 for exchangers, 1190 for high-flow pumps.

B) Unique Customer Gain: Tube sheets, water boxes and pumps rebuilt in place — bi-metallic corrosion prevented.



A tube end sheet rebuilt, overcoated and back in service.

13. 1180 NMB Ceramic Coat

HEAT-EXCHANGER & PUMP PROTECTION

Why overcoat a rebuilt surface with 1180 ceramic coat?

A) Best-in-World Technology: The overcoat for 1170 rebuilds — best protection against erosion and corrosion, impingement, cavitation and bi-metallic attack.

B) Unique Customer Gain: Heat-exchanger tube end sheets, centrifugal, turbine and vacuum pumps, tanks, vessels and gas scrubbers — one rebuild, then years of service.

03 Aerosols

09 PRODUCTS

The maintenance department's first response — in the hand, on the machine, in seconds.



A seized nut released — not cut off.

14. #6030 Pen Oil

HEAVY-DUTY PENETRANT · SAVES TIME

Why keep #6030 Pen Oil for severely seized, rusted assemblies?

A) Best-in-World Technology: Fast, heavy-duty penetration — the deepest rust penetration and re-opening in the world; U.S. Fed. Spec. VV-P-216a; migrates into tight spaces and threads.

B) Unique Customer Gain: Seized assemblies freed fast. If Pen Oil cannot open it, nothing can.

Bonded gasket and paint lifted off, with no damage to the metal.

15. #Z914 Tough Clean

FAST-ACTION, NON-DRIP GASKET & PAINT STRIPPER

Why strip gaskets, paint and carbon with Z914 Tough Clean?

A) Best-in-World Technology: Ultra-strong cleaning action with complete user and metal safety — rapid loosening of all bonded deposits and coatings.

B) Unique Customer Gain: Gaskets off fast; heads and valves cleaned — no damage beneath.

Precision bearings flushed clean without dismantling.

16. #Z939 Bearing Solvent NF

PRECISION PENETRATIVE DEGREASING · CO_2

Why degrease precision bearings with Z939 Bearing Solvent (NF)?

A) Best-in-World Technology: Precision penetrative degreasing — cleans instantly; the pencil jet reaches intricate parts of precision bearings.

B) Unique Customer Gain: Old grease removed in place — enhances bearing life; nothing dismantled.

Caked chain-drive deposits stripped in place.

17. #8485 HD Cleaner & Degreaser

"HIGH FLOW" CITRUS D-LIMONENE

Why clean thick, dried lubricant deposits with 8485 HD Cleaner?

A) Best-in-World Technology: Heavy-duty citrus d-limonene degreaser — High Flow wetting, 360° spray, 97% actives · NF CO_2 propellant.

B) Unique Customer Gain: Thick, dried lube deposits cleaned in place — where standard solutions fail.

Wire gaps sealed — the rope on the left will not rust from within.

18. #7045 HD Open Gear & Wire-Rope Lube

PENETRATES & SEALS WIRE GAPS

Why lubricate open gears and wire ropes with 7045?

A) Best-in-World Technology: A tough, pliable penetrative lubricant — foaming action then a high-tack build guarantees total coverage; moly and graphite fortified; washout-resistant.

B) Unique Customer Gain: Strand wear, snapping and internal rusting prevented — outdoors and in washdown.

A high-speed roller chain that will not throw its lubricant.

19. #90451 Adhesive Chain Lube

PREVENTS CHAIN JAMMING

Why lubricate roller chains with 90451 Adhesive Chain Lube?

A) Best-in-World Technology: Internal-plus-external chain lubrication — extreme adhesion, will not throw off at speed; resists water and steam.

B) Unique Customer Gain: Chains and slideways run without jamming — even underwater, in steam, in dust.

A machined gear train sealed under a self-healing waxy film.

20. #6013 Formula 101 Corrosion Suppressant

5 TO 10 YEARS' PROTECTION

Why protect spares, dies and export shipments with Formula 101?

A) Best-in-World Technology: India's longest-term waxy-film, penetrative, low-surface-tension anti-corrosion coating — self-repairing, solvent-removable; 1,000 hours salt spray.

B) Unique Customer Gain: Spares, dies, export shipments and marine installations protected 5–10 years — washes off when needed.



Valve gear assembled dry — no oil film to hold dust.

21. #6080 Dry Moly Spray

ASSEMBLY LUBE · TO 100,000 PSI

Why use 6080 Dry Moly for assembly, run-in and dusty areas?

A) Best-in-World Technology: Quick-drying with tight adhesion — dry lubrication to 100,000 psi, −100 °F to +700 °F; dielectric.

B) Unique Customer Gain: Assembly and run-in wear and galling reduced; gaskets kept from seizing — best for dusty areas.



Tool-room spares held rust-free through indoor storage.

22. #6007 Rust Inhibitor

LUBE COMPATIBLE

Why protect stored bearings and precision spares with 6007?

A) Best-in-World Technology: Rust and corrosion barrier for indoor storage — fortified lanolin absorbs five times its weight in water; lubricants apply straight over it.

B) Unique Customer Gain: Bearings and spares protected 5+ years indoors — no removal before use.

04 Concrete Repairs & Protection

05 PRODUCTS

Floors, foundations and RCC repaired and sealed between shifts — trafficable in hours.

Floor and foundation cracks filled to 50 MPa; trafficable in four hours.

23. 750 Stanfloor

HIGH-STRENGTH FLOOR & MACHINE-FOUNDATION REPAIR

Why repair floors and machine foundations with 750 Stanfloor putty?

A) Best-in-World Technology: High-strength floor and foundation repair putty — 50 MPa, excellent adhesion to existing concrete.

B) Unique Customer Gain: Trafficable in 4 hours — repaired between shifts, no production loss.

A damaged wall-and-floor junction repaired within the shift.

24. 751 Stanfloor

INSTANT STRUCTURAL CONCRETE REPAIR

Why use 751 Stanfloor for holes, cracks and grouting in concrete?

A) Best-in-World Technology: The world’s best fast-drying, 100% solids, three-component epoxy for holes, cracks and grouting — excellent adhesion to existing concrete.

B) Unique Customer Gain: Trafficable in under 1 hour — instant repair of floors, pillars, beams, columns and storage tanks.

Water beading off a sealed, densified concrete block.

25A. 754 Stangard Sealer

OIL & MOISTURE-TOLERANT PENETRATING CONCRETE SEALER

Why seal concrete with 754 where the substrate is damp or oily?

A) Best-in-World Technology: The world's best penetrating concrete sealer — water- and oil-tolerant; seals capillary voids to practically zero.

B) Unique Customer Gain: Wear, cracking, dusting and water and oil absorption stopped — density and bonding strength added, flooring re-strengthened.

A high-gloss SHP topcoat over sealed surfaces — dust and moisture rejected.

25B. 727 Stangard HP — PLPU SHP

HIGH-GLOSS POLYESTER-PU TOPCOAT

Why finish 754-sealed surfaces with the 727 Stangard HP topcoat?

A) Best-in-World Technology: High-gloss polyester-PU topcoat with SHP — UV tolerant, gloss retaining, easy to re-apply.

SHP edge — repels dust & water: Repels the dust and moisture that dull the surface.

B) Unique Customer Gain: The topcoat for 754 — floors that keep looking, and cleaning, like new.

An RCC tank wall densified against carbonation and seepage.

26. Stangard 753

ANTI-CARBONATION & WATER-SEEPAGE DENSIFYING COATING

Why densify RCC walls, columns, beams and tanks with Stangard 753?

A) Best-in-World Technology: The world's best penetration-cum-densification coating for RCC — stops water ingress, re-strengthens, prevents algae.

B) Unique Customer Gain: Cracking, seepage and growth prevented — 3 to 5 year life minimum.

An expansion joint sealed flexibly against water, chemicals and abrasion.

27. 1311 Stangard Corrokote (FLX)

FLEXIBLE EPOXY SEALING & WATERPROOFING

Why seal expansion joints and metal roofing with 1311 Corrokote (FLX)?

A) Best-in-World Technology: 100% solids flexible epoxy — seals expansion joints and metal roofing; 360–400 microns in two coats; will not crack or peel off.

B) Unique Customer Gain: Long-term sealing with a rubber-like high-gloss finish — takes impact.

05 Higher-Life Synthetic Greases

11 PRODUCTS

100% synthetic. The bearing survives what the seal cannot.

Wet-process bearings that no longer wash out.

28. SL WPG Aquatherm

WATER-WASHOUT RESISTANT · TO 230 °C · 0–1000/1500 RPM

Why grease water-pump bearings with SL WPG Aquatherm?

A) Best-in-World Technology: The world's best 100% synthetic water-pump grease — polymer-reinforced against washout, non-melting.

B) Unique Customer Gain: No bearing failures even if the seals fail — cooling-tower pumps, raw-water pumps, any bearing in contact with water; lubrication cost falls.

ID and FD fan bearings held stable at temperature and speed.

29. Synthox HT

HIGH-TEMPERATURE + HIGH-SPEED · TO 200 °C · 0–2500 RPM

Why lubricate fans and blowers with Synthox HT?

A) Best-in-World Technology: The world's best 100% synthetic HT grease for fans and blowers — double protection: synthetic base plus micronised MoS_2.

B) Unique Customer Gain: ID and FD fans, blower and exhaust fan bearings survive severe shock loads — greasing frequency drops.

A gear coupling that holds its grease under shock load.

30. SL 123R Unitherm

HIGH-LOAD · TO 250 °C · 0–2000 RPM

Why use SL 123R Unitherm on gear couplings and high-load bearings?

A) Best-in-World Technology: The world's best 100% synthetic high-load grease — it will not leak out; takes shock load and extreme pressure.

B) Unique Customer Gain: Gear couplings, billet feeders, planetary mixers, sugar-mill fibrizers and mining machinery run longer on less grease.

HT motor bearings greased with no migration into the windings.

31. Superquiet 100

HT MOTOR GREASE · TO 180 °C · 0–3000 RPM

Why lubricate HT electric-motor bearings with Superquiet 100?

A) Best-in-World Technology: The world's best 100% synthetic HT motor grease — it will not migrate into the windings; PTFE-fortified.

B) Unique Customer Gain: HT motors in ETP plants, heavy machinery and hot, wet areas — no grease-caused failure, no rewinds.

Crane ropes lubricated to the core, against snapping.

32. SL WR2 Wiretherm

SYNTHETIC WIRE-ROPE LUBRICANT · TO 200 °C

Why lubricate wire ropes with SL WR2 Wiretherm?

A) Best-in-World Technology: The world's best 100% synthetic wire-rope lubricant — prevents wear, internal rusting and snapping; penetrates to the core; bitumen-free, never hardens.

B) Unique Customer Gain: Safety against rope snapping — crane ropes last longer, fail safe.

Mineral-based penetration right into the rope core.

33. 70202 Super Wire Rope

MINERAL-BASED WIRE-ROPE LUBE · TO 150 °C

Why choose 70202 Super Wire Rope where a mineral base is preferred?

A) Best-in-World Technology: Fast wetting penetrates to the wire cores — bitumen-free, MoS_2-fortified.

B) Unique Customer Gain: Ropes protected from internal rusting — at mineral-oil economics.

Elastomer seals preserved, not swollen.

34. Siltec HD

O-RINGS & RUBBER SEAL PRESERVATIVE · TO 205 °C

Why preserve O-rings and rubber seals with Siltec HD?

A) Best-in-World Technology: 100% synthetic non-melting rubber preservative — water, steam and chemical resistant; 30 kV/mm dielectric.

Also available: #8035 RC Rubber Care.

B) Unique Customer Gain: O-rings, gaskets and seals last longer — failures prevented, safety enhanced.

A threaded joint sealed positively, without tape.

35. Teflox HD

LEAK-PROOF THREAD SEALING · TO 345 °C

Why seal threaded joints with Teflox HD instead of PTFE tape?

A) Best-in-World Technology: Micro-refined PTFE in a non-melting base — 100% positive sealing on any threaded joint. Superior to PTFE tape.

B) Unique Customer Gain: No leaking threads or flange seals — doubles as gasket parting compound.

Gland packing dressed in place; the shaft is protected.

36. Glandex EP

HIGH-LOAD GLAND DRESSING PASTE · TO 400 °C

Why dress gland packing with Glandex EP?

A) Best-in-World Technology: High-load gland dressing paste applied over existing packing — free of heavy metals, sulphur, lead.

B) Unique Customer Gain: Shaft damage and leakage prevented — no dismantling.

A hot-service stud that will still come apart.

37. Protec Cu-HT

MOLY-COPPER ANTI-SEIZE · −54 °C TO +1200 °C

Why use Protec Cu-HT on hot-service threads and fittings?

A) Best-in-World Technology: Moly-copper anti-seize, −54 °C to +1200 °C — prevents galling, seizing, rusting; highly heat resistant, non-melting.

B) Unique Customer Gain: Studs, bolts and fittings come apart every shutdown — 100% reliable.

A press-fit bearing race assembled without scouring.

38. Molytec EP

MOLY-GRAPHITE ANTI-GALLING ASSEMBLY PASTE · TO 450 °C

Why use Molytec EP on press fittings and moving joints?

A) Best-in-World Technology: Moly-graphite assembly paste — excellent load capacity; protects against fretting and cold welding.

B) Unique Customer Gain: Bearings, wheels and slideways press together smoothly — no seizing, wear or stick-slip, no assembly breakage.

06 Bulk Cleaners & Surface Preparation

07 PRODUCTS

Nothing bonds to dirt. Every coating, wrap and putty downstream starts here.

Industrial floors and machinery cleaned from a single concentrate.

39. #Z101 Alpha 3

GENERAL-PURPOSE HEAVY-DUTY AQUEOUS CLEANER

Why use Alpha 3 as the plant's general-purpose cleaner?

A) Best-in-World Technology: Concentrated heavy-duty aqueous cleaner, neutral in use — machinery, parts and industrial floors.

B) Unique Customer Gain: One concentrate covers the plant — 1:100 light, 1:30 medium, 1:5 heavy.

Ferrous parts degreased and left flash-rust free.

40. #Z101(A) Alpha 5

ANTI-RUST AQUEOUS CLEANER

Why degrease ferrous surfaces with Alpha 5 rather than a plain cleaner?

A) Best-in-World Technology: Heavy-duty rust-inhibited aqueous cleaner, near neutral — a dry transparent film gives short-term rust prevention on ferrous surfaces; biodegradable.

B) Unique Customer Gain: Parts come out clean and stay clean until the next operation.



AC coils and fins cleaned without etching the aluminium.

41. #Z102 Cleanaire 1200

PAINT & ALUMINIUM SAFE CLEANER

Why clean painted machinery, AC coils and fins with Cleanaire 1200?

A) Best-in-World Technology: Paint- and aluminium-safe cleaner — inhibited, soft-metal safe; high-foaming, free-rinsing; no butyl, phosphate or caustic.

B) Unique Customer Gain: AC coils, fins and machinery cleaned at high dilution — safe on plastics.

Cardium compound and tar stripped from open gears.

42. #Z109 Neugenic 4175

THICK, HEAVY DEPOSITS · OPEN GEARS

Why remove solidified deposits with Neugenic 4175?

A) Best-in-World Technology: Non-petroleum semi-aqueous cleaner removes solidified oil, cardium compound, tar and asphalt.

B) Unique Customer Gain: Open gears and heavy machinery stripped clean — concentrate to 1:30.



Rust, oxidation and stain lifted by a hand-applied acid gel.

43A. #Z111 AC-500 Gel Grade

FAST RUST CLEANING · NON-FUMING

Why clean rust and stains with the AC-500 gel grade?

A) Best-in-World Technology: Non-fuming phosphoric-acid gel — rapid rust and stain removal from metal, concrete and tile.

Also available: water-dilutable Dip Grade.

B) Unique Customer Gain: Spare parts, machinery and equipment bodies — apply, wait 10–60 minutes, wash off; no acrid fume.

Rust converted to a sealed blue-black film — the proof that it worked.

43B. #Z704 RUSTEX + #2040(A) Rust Sealer

RUST CONVERTER CUM PRIMER · THE BASE UNDER EVERY SYSTEM

Why convert rust with Z704 RUSTEX rather than paint over it?

A) Best-in-World Technology: Rust converter cum primer — converts rust into a polymer-protected organo-metallic complex; 200 hours' salt spray post conversion; prevents further rust creepage, prepares the surface for paints and coatings.

★ Z704 RUSTEX BASE · 2× LIFE 2026 upgrade — Z704 RUSTEX–NMB (TriArmor): 500+ hours salt spray with epoxy topcoat; around 2× life for every system on it.

B) Unique Customer Gain: Pump casings, pipelines, boilers, tanks and spares stored outside — years more life, and every coating over them lasts longer.



Scale and rust off copper fin tube — safely, with no acrid fume.

44. #Z112 Acidifoam

ALUMINIUM, COPPER & SKIN SAFE ACID CLEANER

Why descale with Acidifoam instead of raw hydrochloric acid?

A) Best-in-World Technology: Complexed "safe" hydrochloric-acid cleaner — more aggressive than phosphoric, no acrid fumes, gentle on skin.

B) Unique Customer Gain: Scale and rust off faster — free rinsing, no phosphate effluent.

Heavy scaling circulated out of an exchanger — no strip-down.

45. #Z118 EQC-10

HEAVY-DUTY RUST & SCALE REMOVER

Why circulate EQC-10 through exchangers, condensers and jackets?

A) Best-in-World Technology: Liquid acid scale remover for exchangers, condensers and jackets — non-flammable, non-fuming.

B) Unique Customer Gain: Complex equipment cleaned without disassembling — heavy scaling and rust circulated out of heat exchangers and heavy engine radiators.

07 Low-Heat Repair Welding

07 PRODUCTS

Defect-free repairs at the industry's lowest heat input — first time in India.

A heavy MS casting repaired — defect-free, on rusty, dirty steel.

46. Super Stanalloy ST 22

MS & CARBON-STEEL REPAIR

Why weld mild-steel and carbon-steel repairs with ST 22?

A) Best-in-World Technology: First time in India — defect-free MS repairs. Ultra-low hydrogen, no hydrogen-induced cracking; self-lifting slag; spatter-free arc; all-position.

B) Unique Customer Gain: No porosities even on rusty, dirty MS — right the first time.

Manganese-steel liners rebuilt without cracking.

47. Super Stanalloy EM 35

MANGANESE STEEL & HIGH-IMPACT REPAIR

Why use EM 35 on manganese steel and high-impact repairs?

A) Best-in-World Technology: First time in India — defect-free Mn-steel and high-impact repairs; joins Mn steel to carbon steel; strong, tough deposits with out-of-position capability.

B) Unique Customer Gain: The ductile deposit will not crack — crushers and liners back in service.

A die-steel component repaired with no HAZ cracking.

48. Super Stanalloy DS 34

UNKNOWN, DISSIMILAR, DIE, FORGED & CAST STEELS

Why hold DS 34 for repairs on steels nobody can identify?

A) Best-in-World Technology: First time in India — defect-free repairs of unknown, dissimilar, die and cast steels; ferrite-balanced chemistry gives crack-free weld deposits on HAZ-prone steels.

B) Unique Customer Gain: Tough, high crack resistance, all-position — the emergency electrode when the metal is unknown and the machine has to run.

A cast-iron cylinder head welded cold — no oven, no distortion.

49. Super Stanalloy FN 62

CAST-IRON REPAIR WITHOUT PRE-HEATING

Why repair cast iron with FN 62 rather than pre-heating the casting?

A) Best-in-World Technology: First time in India — defect-free cast-iron repairs without pre-heating; highest tensile strength in class, lowest heat input; high resistance to oil and grease contamination.

B) Unique Customer Gain: It will not crack — heads and housings repaired on the machine, no oven, no distortion.

An emergency high-temperature repair — no PWHT required.

50. Super Stanalloy TC 42

UNIVERSAL & HIGH-TEMPERATURE EMERGENCY REPAIR

Why keep TC 42 for emergencies on any unknown metal combination?

A) Best-in-World Technology: First time in India — one defect-free electrode for any unknown combination; strong, tough deposits with strength under thermal cycling; no PWHT.

B) Unique Customer Gain: All ferrous metals joined with no re-work — exactly when downtime is the issue.



A clean U-groove gouged at low amperage and low HAZ.

51. Super Stan Gouge

LOW-AMPERAGE GOUGING

Why prepare the groove with Super Stan Gouge before the repair begins?

A) Best-in-World Technology: 100% defect-free gouging at low amperage and low HAZ — white smoke shows cracks as you gouge.

B) Unique Customer Gain: Superb U-grooves, minimal cleaning — the defect fully removed before the weld.



Any metal cut with a stick electrode — low HAZ, no gas set.

52. Super Stan Cut

LOW-AMPERAGE CUTTING

Why cut with Super Stan Cut instead of setting up gas?

A) Best-in-World Technology: 100% defect-free cutting at low amperage and low HAZ — easy cutting, no electrode overheating to the end; any metal.

B) Unique Customer Gain: Cut any metal off the same welding set — no gas cylinders, no permit chain.

FROM FAILURE TO RETURN-TO-SERVICE

ONE VENDOR. ONE WARRANTY. OUTCOMES GUARANTEED.

52 mechanical and civil maintenance solutions across seven categories - built to repair, protect and keep the plant running.

www.stanvac.com · +91-8527-1998-11 · sales@stanvac.com · digitalmktg@stanvac.com

Performance figures are from in-house testing, published technical data sheets and independent corrosion research.
Application data, coverage and service life depend on substrate condition, surface preparation and site conditions.

STANVAC CHEMICALS (INDIA) LTD.
Plot No. 551, Sector-37, Pace City-II, Gurugram, Haryana - 122001, India