Stanvac
உலகளவில் போட்டியிடும் போட்டியாளர்

22-STANVAC TURNKEY SERVICES

உலகளவில் போட்டியிடும் திறனுடன் தொழில்துறை செயல்பாட்டு தீர்வுகளை வழங்குதல்

உற்பத்தியை அதிகரிக்கவும்
- Cable Sectional
- Cable Accessories
- Factory Setup
- Automation Solutions
- Instrument And Protection
- Energy Saving Thermal Coatings

தரம் குறைவு
- Production Machinery Fine Tuning
- Product Test Machinery
- Quality Control Instruments
- Factory Inspection Production Line Improvement
- Energy Saving Thermal Coatings

தொழில் பாதுகாப்பு
- Cable Tunnel Cabinet
- Safety Protection Equipment
- Factory Safety Training
- Public Crossing System

சேவை மேம்பாடு
- Cable Accessories
- Software And Hardware
- New Energy Car Charging Pile Solutions

தரச் சான்றிதழ்
- ISO 9001 Certification

தூரிய பெயர்ப்பு தூரிய வாரண்டி, முழுமை கூறுதி

Stanvac Chemicals India LLP

1. தூ & பின்னாடி குறிப்பாக

STANVAC CABLE SURVIVAL™

தொழில்நுட்பம் பெயர்: Cable Survival Coating — Nano + Ceramic Composite Thermal Barrier

DMT: 120 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 2 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on, Dip-coat | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

STANVAC PANEL FIRE INTEGRITY™

தொழில்நுட்பம் பெயர்: Panel Fire Integrity Coating — Intumescent + Ceramic Composite

DMT: 90 Minutes @ 1,100°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 1.5 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–1.5 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

2. தூ & பின்னாடி குறிப்பாக

STANVAC FIRESTOP BARRIER™

தொழில்நுட்பம் பெயர்: Multi-Purpose Fire Barrier Kit — Fill, Void or Cable Transit

DMT: 180 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 3 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Pre-formed modules, Putty, Spray | Thickness: 50–150 mm | Flexibility: Modular, reusable | Adhesion: Excellent bond to concrete, steel, cable jacket | Environmental: Non-toxic, halogen-free | Lifespan: 20+ years

STANVAC DIELECTRIC FLOORING™

தொழில்நுட்பம் பெயர்: Dielectric Rubber Mat — Anti-Slip Textured Mat

DMT: 10,000 Volts (10 kV) | Flame Spread: 0 (ASTM D2863) | Fire Resistance: Self-Extinguishing | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Floor mat, Roll-out | Thickness: 3–6 mm | Flexibility: Flexible, rollable | Adhesion: Non-slip textured surface | Environmental: Non-toxic, halogen-free | Lifespan: 10+ years

3. தூ & பின்னாடி குறிப்பாக

STANVAC SWITCHGEAR / HV FLASHOVER PROTECTION™

தொழில்நுட்பம் பெயர்: HV Flashover Protection Coating — Silicone + Ceramic Composite

DMT: 60 Minutes @ 1,000°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 1 Hour (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–1.5 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

STANVAC TRANSFORMER GUARD™

தொழில்நுட்பம் பெயர்: Transformer Protection Coating — Intumescent + Ceramic Composite

DMT: 120 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 2 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

4. தூ & பின்னாடி குறிப்பாக

STANVAC BATTERY / UPS BANK PROTECTION™

தொழில்நுட்பம் பெயர்: Battery Room Protection Coating — Intumescent + Ceramic Composite

DMT: 120 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 2 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

5. தூரு குடியிப பூமியகம்

STANVAC RUSTED ASSET RECOVERY™

தொழில்நுட்பம் பெயர்: Oil-Based Rust Converter + Anti-Rust Primer

DMT: 240 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 4 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

தூரு தூரிய குறிப்பாக

STANVAC 6 ACID / MARINE PROTECTION™

தொழில்நுட்பம் பெயர்: 6% HF Resistant Epoxy + 2% Fluoride + 500 Hour Salt Spray

DMT: 120 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 2 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

STANVAC EXPORT SHIPMENT PROTECTION™

தொழில்நுட்பம் பெயர்: Export Grade Anti-Corrosion Coating — Wax + Polymer Composite

DMT: 240 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 4 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

தூரு தூரிய குறிப்பாக

STANVAC GI / GALVANIZING REVIVAL™

தொழில்நுட்பம் பெயர்: Zinc-Rich Epoxy Primer — 95% Zinc Content

DMT: 120 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 2 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

STANVAC ENERGY-SAVING THERMAL COATING™

தொழில்நுட்பம் பெயர்: Ceramic Microsphere Insulation Coating — Water-Based

DMT: 120 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 2 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

தூரு தூரிய குறிப்பாக

STANVAC PRODUCTION MACHINERY FAST REPAIRTM™

தொழில்நுட்பம் பெயர்: Metal-Ceramic Composite Repair Compound — Two-Part Epoxy

DMT: 240 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 4 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

III. கோல்ட் சிப்பிள் குறிப்பாக

STANVAC PIPELINE INTEGRITY™

தொழில்நுட்பம் பெயர்: Anti-Fatigue & Leak Prevention Coating — Epoxy + Ceramic Composite

DMT: 120 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 2 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

கோல்ட் சிப்பிள் குறிப்பாக

STANVAC EMERGENCY LEAK-STOP KIT™

தொழில்நுட்பம் பெயர்: Multi-Purpose Emergency Repair Kit — Epoxy + Ceramic Composite

DMT: 240 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 4 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

STANVAC HEAT EXCHANGER LIFE™

தொழில்நுட்பம் பெயர்: Heat Exchanger Protection Coating — Epoxy + Ceramic Composite

DMT: 120 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 2 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

கோல்ட் சிப்பிள் குறிப்பாக

STANVAC TANKAGE REHABILITATION™

தொழில்நுட்பம் பெயர்: Tank Lining — Epoxy + Ceramic Composite

DMT: 120 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 2 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

IV. தூரு & கார்ன்பிரீட் குறிப்பாக

STANVAC NLC LIFE EXTENSION™

தொழில்நுட்பம் பெயர்: NLC Protection Coating — Epoxy + Ceramic Composite

DMT: 120 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 2 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on | Thickness: 0.5–2.0 mm | Flexibility: Retains flexibility after curing | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

V. இண்டஸ்ட்ரிக்கு தனிபட பவர்ன் சேவைகள்

STANVAC DATA CENTER UPTIME™

தொழில்நுட்பம் பெயர்: Cable Survival + Flame Fire Immunity + Thermal Barrier + Protective Coating + Ventilation Control + Monitoring + Alarm System

DMT: Fire: 90 / 120 / 180 / 240 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 1.5 / 2 / 3 / 4 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on, Pre-formed modules, Putty | Thickness: 0.5–2.0 mm / 50–150 mm | Flexibility: Retains flexibility after curing / Modular, reusable | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

STANVAC SOLAR FARM PROTECTION™

தொழில்நுட்பம் பெயர்: Solar Cable Survival + Flame Fire Immunity + Thermal Barrier + Protective Coating + Ventilation Control + Monitoring + Alarm System

DMT: Fire: 90 / 120 / 180 / 240 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 1.5 / 2 / 3 / 4 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on, Pre-formed modules, Putty | Thickness: 0.5–2.0 mm / 50–150 mm | Flexibility: Retains flexibility after curing / Modular, reusable | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

இண்டஸ்ட்ரிக்கு தனிபட பவர்ன் சேவைகள்

STANVAC RAILWAY / METRO TRACTION™

தொழில்நுட்பம் பெயர்: Railway Cable Survival + Flame Fire Immunity + Thermal Barrier + Protective Coating + Ventilation Control + Monitoring + Alarm System

DMT: Fire: 90 / 120 / 180 / 240 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 1.5 / 2 / 3 / 4 Hours (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on, Pre-formed modules, Putty | Thickness: 0.5–2.0 mm / 50–150 mm | Flexibility: Retains flexibility after curing / Modular, reusable | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

STANVAC HVAC / COOLING SYSTEM SERVICE™

தொழில்நுட்பம் பெயர்: HVAC Duct Cleaning — Coil Cleaning — Filter Replacement — Air Quality Testing — Chemical Treatment — Preventive Maintenance — Emergency Service — Annual Contract

DMT: 60 Minutes @ 1,200°C | Flame Spread: 0 (ASTM E84) | Fire Resistance: 1 Hour (UL 1709) | Smoke Density: Ultra-Low | Toxic Gas Emission: Near-Zero | Application: Spray-on, Brush-on, Pre-formed modules, Putty | Thickness: 0.5–2.0 mm / 50–150 mm | Flexibility: Retains flexibility after curing / Modular, reusable | Adhesion: Excellent bond to metal, concrete, cable insulation | Environmental: Non-toxic, halogen-free | Lifespan: 15+ years

Plot No. 152, Road No.2, Sector-IV, Gurugram Haryana - 122001, India
Website : www.stanvac.com
Contact : +91 9999 000 000 | info@stanvac.com